

AAC AUS-CLEAN

Tank and Equipment Cleaner

AAC AUS-CLEAN is an all-purpose, biodegradable spray tank, machine and equipment cleaner. Specially designed for decontaminating cleaning equipment, AUS-CLEAN eliminates the adverse affects of chemical residues that often cause crop damage.

APPLICATION RATES:

General Cleaning

Rate: 1 part AUS-CLEAN to 50 parts water.

Strengthen / weaken as required.

Stubborn Stains On Tanks And Machinery

Rate: 1 part AUS-CLEAN to 50 parts water.

Scrub the offending areas vigorously using a stiff scrubbing brush.

Vehicles

Rate: 1 part AUS-CLEAN to 10 parts water.

Spray on surface - allow to stand (overnight if possible). Hose off with water.

Degreaser

Rate: 1 part AUS-CLEAN to 1 part Kerosene - mix well to form emulsion

Brush on to affected area. Allow to stand until grease etc. is broken down.

Hose off with water.

DIRECTIONS FOR USE: General Use

Flush out sprayer with clean water. Half fill the spray tank and commence agitation. Slowly add the required quantity of AUS-CLEAN. Top up the tank and agitate vigorously for 15 minutes. Use hand lance or return hose (where suitable) to clean top around filter basket etc. Open spray booms and spray out. With persistent chemicals, or when cleaning out at the end of season, allow mixture to stand overnight before spraying out. When sprayer is to be reused immediately, re-fill the tank with water, agitate for 5 minutes and spray out. When storing sprayer for any length of time, do not give final rinse until required for use as AUS-CLEAN leaves a protective film..